



2022 NSF IUCRC CICI- IAB Fall Meeting TAMU Site Projects' Summaries



2022 NSF IUCRC CICI- IAB Fall Meeting TAMU Site Projects' Summaries

TAMU - 5: Evaluating the Performance of Fiber-Based Concrete Mixes for Various Applications	3
TAMU - 6: Application of Geofoam in Thermal Encapsulation of Foundations	5
TAMU - 7: Design and Testing of IFI Geosynthetic Products	7
TAMU - 8: Performance of Pavement Sections with Wicking Geosynthetics	9

TAMU - 5: Evaluating the Performance of Fiber-Based Concrete Mixes for Various Applications

Program Manager / PI: Dr. Anand J Puppala

Company / Sponsor: Warstone Innovations, LLC

I/UCRC Executive Summary - Project Synopsis		Date: December 5th, 2022
Center/Site: Center for the Integration of Composites into Infrastructure (CICI) / TAMU		
Tracking No.:	Phone: () -	E-mail: anandp@tamu.edu
Center/Site Director: Dr. Anand J Puppala		Type: Introducing
Project Leader: Dr. Surya S.C. Congress, Krishneswar Ramineni (Doctoral Student) and Dr. Anand J Puppala		Proposed Budget: \$ 30,000
Project Description: <p>Rising seawater levels and increased frequency of high intensity storms due to climate change is a serious concern for the coastal areas. These factors make coastal areas vulnerable to flooding, coastal erosion, and water pollution causing damage to infrastructure assets and human lives. Traditionally sandbags are used as barriers to control the destructive behavior of flooding and stormwater. These sandbag barriers are typically designed to take the impact, from the hydraulic forces of the storm and the debris flowing in the storm, and protecting physical assets and communities. Preliminary findings from the interactions with the industry indicated that sandbags have some limitations in terms of handling and transportation. Moreover, sandbags deteriorate when they are exposed for prolonged alternate wetting and drying cycles. The limitations of this existing practice offered the need for exploring the application of the matrix of fiber-based concrete mix bags, patented by Warstone Innovations LLC, for various coastal purposes. So, this project currently focuses on evaluating the performance of various fiber-based concrete mix bags as flood barrier materials.</p>		
Experimental plan: The preliminary testing includes evaluating the physical and chemical properties of concrete constituents. Based on material properties, fiber-based concrete mix proportions are prepared, and the fiber dosage is optimized considering the physical and durability tests. Wetting and drying studies will be conducted under two different temperatures (40°C and 4°) and also separately by using artificially prepared seawater. Expansion tests will be performed to evaluate the expansion behavior of the mixes. For the second phase of testing, a large-scale laboratory box size 3' x 3' x 4' is constructed to evaluate the performance of the fiber-based concrete mix bags in similar conditions mentioned above.		
Related work elsewhere: Sand filled bags are used as erosion barriers during flooding. Research studies were performed to optimize the natural fiber dosage in cement-concrete and for structural applications. Not much work was conducted on evaluating the performance of fiber-based concrete mixes as erosion barriers in various conditions. This project focuses on developing a system to use fiber-based concrete mix filled bags as an efficient alternative to sandbags and prevent the damage due to flooding.		
How this project is different: There have been many past studies that used natural fibers in concrete to improve mechanical properties like compressive strength and flexural strength. The fiber dosage is limited to		

<p>a maximum of 10% weight of cement mixture. But this project focuses on developing fiber-based concrete mixture that can contain more than 50% weight of cement mixture to address flooding and erosion issues.</p>	
<p>Milestones for the current proposed year: During this year, permeability studies will be performed on fiber based concrete mixes and large scale laboratory box setup to study the performance of fiber-based concrete mix bags against hydraulic forces in various conditions.</p>	
<p>Deliverables for the current proposed year: A report with preliminary findings emphasizing fiber dosage optimization based on wetting and drying studies in various conditions will be provided.</p>	
<p>How the project may be transformative and/or benefit society: The research findings of this project will provide an idea about the feasibility of using fiber-based concrete mix bags to reduce the damage caused due to flooding and erosion. This will help in enhancing the resilience of communities, especially located in coastal corridors.</p>	
<p>Research areas of expertise needed for project success: Extensive knowledge in concrete technology and different microstructural techniques to understand cement chemistry. Adept knowledge of coastal flooding and erosion. A good understanding of solid and fluid mechanics.</p>	
<p>Potential Member Company Benefits: Identify optimum fiber-based concrete mix through a comprehensive laboratory testing plan. Explore various applications of these mixes to address other infrastructure related areas.</p>	
<p>Progress to Date: Material properties of concrete constituents were evaluated, and fiber-based concrete mix proportions were identified. Wetting and drying tests using potable water at 20°C and 50 relative humidity (RH) were completed. Wetting and drying studies at 40°C and 4°C and using saltwater water are completed. Currently, performing permeability tests on fiber based concrete mixes.</p>	
<p>Estimated Start Date: 08/01/2021</p>	<p>Estimated Knowledge Transfer Date: 08/31/2023</p>

TAMU - 6: Application of Geofoam in Thermal Encapsulation of Foundations

Program Manager / PI: Dr. Anand J Puppala

Company / Sponsor: Thermafoam

I/UCRC Executive Summary - Project Synopsis		Date: December 5th, 2022
Center/Site: Center for the Integration of Composites into Infrastructure (CICI) / TAMU		
Tracking No.:	Phone: () -	E-mail: anandp@tamu.edu
Center/Site Director: Dr. Anand J Puppala		Type: Continuing
Project Leader: Dr. Surya S.C. Congress, Hiramani Raj Chimaurya (Doctoral Student) and Dr. Anand J Puppala		Proposed Budget: \$45,000
Project Description: The main objective of the research work in this project is to mitigate temperature fluctuations within dwellings by designing and using thermally insulated and energy efficient novel foundation systems. Temperature fluctuations inside the dwellings typically occur from advection, diffusion and radiation at foundation joints; therefore, an insulation material around dwelling foundation systems would help in reducing these temperature fluctuations. The proposed research plan will explore the use of expanded polystyrene geofoam material as a thermal insulating material for two foundation alternatives or systems to assist the building infrastructure in conserving energy. The proposed research study attempts to identify and optimize the design and construction of foundation insulation systems using geofoam materials, which are cost-effective and provide resilient support. The novelty of the proposed research lies in the use of geofoam for thermally encapsulating residential dwellings, at low additional cost and minimal deviation from the standardized structural and architectural design and construction of residential dwellings.		
Experimental plan: Two different types of insulated foundation systems, viz., (a) Geofoam blocks attached around the periphery of foundation (referred here to as GAF system), and (b) Geofoam slab placed underneath the foundation system (referred here to as GBF system) will be constructed in the laboratory. Temperature sensors will be installed both inside and outside of the structure to monitor the variation in temperature and heat transfer over time. The results will be compared with that of the control prototype to study the effect of thermal encapsulation and energy savings. The cost benefit analysis will also be conducted as a part of this study.		
Related work elsewhere: The insulating properties of EPS Geofoam have been studied earlier in brevity, however, its efficiency to provide thermal insulation to dwelling has not been evaluated in detail.		
How this project is different: The insulating properties of EPS geofoam are known, however, its application for saving energy consumption of dwelling needs to be evaluated. In this study, various sizes and types of EPS Geofoam blocks are being used for encapsulating the foundation of a dwelling prototype and evaluating its performance related to energy transfer.		
Milestones for the current proposed year: During this year, the lab scale study will be continued for different thicknesses, configurations, and grades of geofoam. Numerical simulations will also be conducted in conjunction with the experiments to model a wider range of scenarios of thermal encapsulation using Geofoam material.		
Deliverables for the current proposed year: Report with preliminary findings of the energy efficiency of the dwelling prototype with Geofoam-encapsulated foundation.		
How the project may be transformative and/or benefit to society: The energy savings from the insulation would allow the owner to recoup the cost of foundation insulation systems quickly. Subsequently, with a large number of dwellings adopting such a foundation system, the lower power consumption costs of each of these dwellings would collectively help in reducing the energy loads on		

power grid. Supporting the reduced energy needs of these modified dwellings with other renewable energy sources such as solar energy will achieve net-zero energy status for most dwellings. Apart from the economic benefits of these foundation insulation systems, the foundation systems can also promote the development of sustainable infrastructure, namely green buildings and zero-energy ready homes.

Research areas of expertise needed for project success: The knowledge of thermodynamics involved in evaluating the energy transfer in homes during warm and cooler climatic conditions and use of cost-effective construction materials and techniques is required for the study.

Potential Member Company Benefits: The study on thermal encapsulation of the foundation using EPS Geofoam will be able to provide design guidelines for full-scale pilot studies or future construction on thermal insulation of buildings with Geofoam-encapsulated foundation.

Progress to Date: First set of tests on geofoam insulated footing was performed for geofoam-below-footing (GBF) configuration. Numerical modeling of the control test was performed using COMSOL Multiphysics. Testing using other configurations and grades of geofoam is ongoing.

Estimated Start Date: 09/01/2020

Estimated Knowledge Transfer Date: 08/31/2023

TAMU - 7: Design and Testing of IFI Geosynthetic Products

Program Manager / PI: Dr. Anand J Puppala

Company / Sponsor: Industrial Fabrics (IFI)

I/UCRC Executive Summary - Project Synopsis		Date: December 5th, 2022
Center/Site: Center for the Integration of Composites into Infrastructure (CICI) / TAMU		
Tracking No.:	Phone: () -	E-mail: anandp@tamu.edu
Center/Site Director: Dr. Anand J Puppala		Type: Continuing
Project Leader: Dr. Md Ashrafuzzaman Khan, Krishneswar Ramineni (Doctoral Student) and Dr. Anand J Puppala,		Proposed Budget: \$140,000
<p>Project Description: The application of geosynthetic products can provide an effective solution for the earth retaining systems as well as different foundation systems by reinforcing the earth materials. These products include, but not limited to, geocells, geogrids, and laminated geogrid products. The combination of these products has been used in the field for quicker construction and better performance. However, there are no such guidelines available regarding the design of such products. Giroud and Han (2004) provide a design methodology for geogrid reinforced pavement structures. The objective of this study is to expand on those methods by improving the study behind the theories and/or incorporating new concepts and methods of calculations. There are two major objectives in this study: Part I: Performing repeated load tests on geosynthetic reinforced base layers built on different weak subgrades and then use the test data to calibrate parameters that can be used with Giroud and Han (G&H) designs. Part II: Developing various design charts and methods for IFI, Inc Geosynthetic Products based on the results and calibration studies from Part I.</p>		
<p>Experimental plan: Physical and engineering soil testing including grain size distribution, standard Proctor test, Atterberg's limit, resilient modulus, shear strength and undrained strength tests, and California Bearing Ratio (CBR) test has been performed on the base material and subgrade soils. Both these materials were selected based on the recommendation by IFI, Inc. For subgrade selection, the subgrades with different CBR values (1 and 3) were prepared by adjusting the moisture content. A large-scale test setup is available at the Center for Infrastructure Renewal (CIR), Texas A&M University, which was designed and constructed to facilitate a wide range of static and repeated load testing to evaluate the behavior and performance of the geosynthetic reinforced soils. The large-scale test setup consists of a steel testing box, loading frame, actuator, along with a data acquisition system. The steel testing box has dimensions of 6 ft x 6 ft x 5 ft (1.83 m x 1.83 m x 1.52 m). In the test box, subgrade layers of select CBR were prepared using selected material at target dry density and moisture content.</p>		
<p>Test results were analyzed and calibrated to determine various parameters for both geocell and Fabgrid (geocomposites) reinforced soils. Test results from the repeated load tests would be used to generate $1/\tan \alpha$ vs log N plots. This information could be used to calibrate the performance of the section as a function of the Aperture Stability Modulus (J) for proposed Fabgrid. Analyses of these results would provide calibration parameters that will be useful for designing reinforced base/subbase systems using IFI geosynthetic products.</p>		
<p>Related work elsewhere: The longevity and performance of the pavement sections on problematic soils including soft and expansive subgrades, has been a major concern for transportation practitioners (Puppala et al. 1996; Puppala and Pedarla 2017). Flexible pavements and unpaved roads constructed on problematic soil suffer from different failures such as cracking, rutting, and depression (George et al. 2019; Khan et al. 2020; Puppala et al. 2017). The reasons for such failure may be attributed to fatigue, temperature changes, moisture ingress and egress, and softening caused by surface layer cracking (Han</p>		

<p>et al. 2011, Pokharel et al. 2018). The use of geosynthetics as an additional supporting layer to the existing subsoil might help the agencies and organizations to eliminate the distress problems associated with the problematic soils (Giroud and Noiray 1981).</p>	
<p>How this project is different: In the previous studies, researchers used planar geosynthetic products or the combination of two/three different geosynthetic products; however, there is very little information available about the utilization of combined products such as FabGrid. This study focuses on the utilization of different combinations of high-density polyethylene (HDPE) products for different types of foundation systems.</p>	
<p>Milestones for the current proposed year: Conducting tensile strength tests on different types of geogrid products. Completed all the required large-scale tests: 2 unreinforced and 16 reinforced sections. Dynamic cone penetrometer (DCP), handheld PANDA DCP, and Lightweight deflectometer (LWD) tests were also conducted to determine the stiffness of the base and subgrade materials. The Results obtained from different test sections were used to develop the correlation between the stress distribution angles with the strength and stiffness properties of different geosynthetic products.</p>	
<p>Deliverables for the current proposed year: Load-deformation characteristic curves of the unreinforced and reinforced sections constructed with CBR=1 & CBR=3 will be reported. The test results obtained from different types of soils and geogrids will be considered to calibrate the existing G-H model. Preliminary design charts will be reported for the geogrid reinforced sections.</p>	
<p>How the project may be transformative and/or benefit society: This study mainly focuses on the utilization of new combinations of HDPE products (e.g., Fabgrid and Fabgrid+GeoCell). This study aims to develop design charts for different HDPE products/combinations of HDPE products for different stiffnesses of foundation materials. The outcome of this research will help to ensure the safety and reliability of the geotechnical structures by providing the design charts.</p>	
<p>Research areas of expertise needed for project success: A thorough knowledge in foundation design using geosynthetics reinforcement, pavement engineering and load transfer mechanisms with different combinations of HDPE products.</p>	
<p>Potential Member Company Benefits: Development of design guidelines for foundation systems with different combinations of HDPE materials.</p>	
<p>Progress to Date: Performed material characterization of base and subgrade materials in the laboratory. Performed large-scale repeated load tests for 16 reinforced and 2 unreinforced sections. Developed the preliminary models to accommodate the stiffer geogrid materials. Developed preliminary design charts for unreinforced and reinforced sections.</p>	
<p>Estimated Start Date: 9/1/2020</p>	<p>Estimated Knowledge Transfer Date: 8/31/2023</p>

TAMU - 8: Performance of Pavement Sections with Wicking Geosynthetics

Program Manager / PI: Dr. Anand J Puppala

Company / Sponsor: TenCate

I/UCRC Executive Summary - Project Synopsis		Date: December 5th, 2022
Center/Site: Center for the Integration of Composites into Infrastructure (CICI) / TAMU		
Tracking No.:	Phone: () -	E-mail: anandp@tamu.edu
Center/Site Director: Dr. Anand J Puppala		Type: Continuing
Project Leader: Dr. Nripojyoti Biswas (Post Doc) and Dr. Anand J Puppala		Proposed Budget: \$160,000
<p>Project Description: Expansive soils are found in various regions around the globe. In the US itself, expansive soils cover a vast stretch in western and southwestern states. The seasonal moisture variation leads to a large volume change in these soils causing alternate swelling and shrinkage. As a result, this induces significant surficial distress in the form of heaving and cracking. The Mirafi H2Ri is an innovative geosynthetic product that integrates the features of traditional woven geosynthetics like strength, separation, and puncture resistance to an additional water-wicking capability with the presence of hydrophilic and hygroscopic fibers. These woven geotextiles have the capability to be utilized in various applications including pavement sections, where they can be used as a separation between the base and subgrade while providing drainage through the geotextile.</p> <p>The main objective of the proposed project is to study the separation and drainage characteristics of woven geotextile Mirafi H2Ri when introduced between base and subgrade layers of the pavement section. Full-scale field implementation of the geotextile on the eastbound FM 1807 in Venus, Texas was constructed. In addition, small-scale laboratory tests in a controlled environment will be performed to understand the moisture movements in subsoil due to the placement of H2Ri. A numerical model will be developed to compare experimental data obtained from the laboratory and field test sections with the model predictions. Additionally, the life cycle cost analysis (LCCA) will be performed and compared with other traditional materials used for the construction of pavement sections. Finally, the benefits of using the H2Ri geosynthetic in pavement sections having high plasticity soils as subgrades will be evaluated and summarized in the final report.</p>		
<p>Experimental plan: The study focuses on the installation and monitoring of TenCate Mirafi H2Ri between the subgrade and the base layers on the eastbound FM 1807 in Venus, Texas. Field data for the past year was obtained from two test sections, (i) RAP aggregate as a base layer, and (ii) traditional flex-base aggregate as a base layer and their performance was compared with a control section. Instrumentation such as moisture probes, pressure cells, and Shape Array Accelerometer (SAA-MEMS) were installed for continuous monitoring of the test sections. The influence of variation in moisture, traffic loads on the stresses developed on top of the subgrade layer was measured and evaluated and is expected to continue in the coming years.</p> <p>Furthermore, the wicking action of the TenCate Mirafi H2Ri, when embedded in expansive soil subgrade, is being studied by performing small-scale laboratory tests. Numerical models will be developed and validated against the experimental data obtained from the laboratory and field test sections. LCCA will be performed and compared with pavement sections built with conventional construction materials.</p>		
<p>Related work elsewhere: The effectiveness of wicking geotextile in reducing soil moisture for roadway application was studied in a laboratory model by Wang et. al. (2017). Zhang et.al. (2014) studied the</p>		

effect of wicking fabric to prevent the effect of frost boil on Alaskan pavements by performing full-scale field implementation of the woven geosynthetics. The rate of water removal under controlled temperature and humidity using wicking was studied by Guo et.al. (2016).

How this project is different: In the previous studies, H2Ri geotextile was used to mitigate the effects of frost-heaving. This study primarily focuses on the improvement in the drainage of pavement sections by using H2Ri and its application in high plasticity subgrade soils. In addition to the enhancement of drainage coefficient, H2Ri is a high-strength material that would provide adequate support for the base layer.

Milestones for the current proposed year: Performed laboratory studies on different test sections. Tested the efficacy of the wicking fibers in a laboratory environment due to one-way and two-way drainage. In the field sections, performed present condition monitoring studies using falling weight deflectometer (FWD) and lightweight deflectometer (LWD) studies. Developed a sustainability analysis framework.

Deliverables for the current proposed year: Performance evaluation of field test sections with H2Ri geosynthetics. Construction and monitoring results of a small-scale laboratory model. Develop sustainability model.

How the project may be transformative and/or benefit society: This study mainly focuses on the drainage improvement of pavement which will enhance the structural capacity of the pavement system. This new technology will not only increase the drainage coefficient but also enhances overall stiffness which will reduce the required pavement thickness. This project will contribute to enhanced safety to the traveling public and reduced construction costs. It also increases the resiliency and longevity of the pavement systems, thereby contributing to a higher return on investment. Additionally, the use of RAP material can make the pavement structures more sustainable and cost-effective as it will decrease the demand for virgin aggregate.

Research areas of expertise needed for project success: A thorough knowledge in pavement design using Geosynthetics reinforcement, advanced numerical modeling of H2Ri reinforced pavements under static and repeated loadings, sustainability of RAP bases with H2Ri in the pavement construction, and the estimation of cost-effectiveness of pavement constructed with RAP material on expansive subgrade soil.

Potential Member Company Benefits: Development of design and construction guidelines for H2Ri supported pavements with RAP base in areas where the subgrade soil is expansive. Pavement structures will be resilient and will have lesser distress during their service life.

Progress to Date: The laboratory studies using the novel geotextile showed that the presence of the wicking fibers improved the drainage capacity of both base and subgrade soil. The depth of influence of the wicking fibers extended to more than 10 inches in the subgrade soil. Additionally, two-way drainage was more effective in removing layer moisture as compared to one-way drainage. In the field sections, the falling weight deflectometer studies showed higher modulus values in sections with reclaimed asphalt pavement aggregates as compared to crushed stone aggregates. The LWD studies also provided similar results as the FWD studies. Sustainability analyses of the method was performed.

Estimated Start Date: 5/1/2018	Estimated Knowledge Transfer Date: 1/31/2023
---------------------------------------	---